

**CERTIFICATE OF QUALITY****KEKKILÄ OPM 525 W CL R6065****COMPOSITION**

Peat raw material	Sphagnum peat 1.00 m <sup>3</sup>
Coarseness	Medium-Coarse
Production screening	5–25 mm
Other constituents	Clay granulate 20.00 kg/m <sup>3</sup>

**ADDITIVES**

KS1 N-P<sub>2</sub>O<sub>5</sub>-K<sub>2</sub>O 15-12-29 1.00 kg/m<sup>3</sup>  
Limestone (Ca,Mg) 4.07 kg/m<sup>3</sup>  
Wetting agent 0.11 l/m<sup>3</sup>

**PHYSICAL PROPERTIES**

Moisture content (EN 13040) 50 - 60 %  
Dry bulk density (EN 13041) 80 - 120 g/l

**CHEMICAL PROPERTIES**

pH H<sub>2</sub>O (EN 13037) 5,9 (5,4 - 6,9)  
Electrical conductivity EC (EN 13038) 32 (16 - 48) mS/m

**MANUFACTURER**

Kekkilä Oy, Ratatie 11, FI-01300 Vantaa, Finland [www.kekkilaprofessional.com](http://www.kekkilaprofessional.com)

**COUNTRY OF MANUFACTURING**

Manufactured in Estonia