

**CERTIFICATE OF QUALITY****KEKKILÄ TSM 2 W R6012****COMPOSITION**

Peat raw material	Black peat 0.50 m <sup>3</sup> Sphagnum peat 0.50 m <sup>3</sup>
Coarseness	Fine
Production screening	0–6 mm
Other constituents	

**ADDITIVES**

KS1 N-P<sub>2</sub>O<sub>5</sub>-K<sub>2</sub>O 15-12-29 1.00 kg/m<sup>3</sup>  
Limestone (Ca,Mg) 3.52 kg/m<sup>3</sup>  
Wetting agent 0.11 l/m<sup>3</sup>

**PHYSICAL PROPERTIES**

Moisture content (EN 13040) 55 - 75 %  
Dry bulk density (EN 13041) 85 - 125 g/l

**CHEMICAL PROPERTIES**

pH H<sub>2</sub>O (EN 13037) 5.9 (5.4 - 6.9)  
Electrical conductivity EC (EN 13038) 32 (16 - 48) mS/m

**MANUFACTURER**

Kekkilä Oy, Ratatie 11, FI-01300 Vantaa, Finland [www.kekkilaprofessional.com](http://www.kekkilaprofessional.com)

**COUNTRY OF MANUFACTURING**

Manufactured in Estonia