

PRODUCT INFORMATION**KEKKILÄ TSM 2 W R6012**

Kekkilä Professional supplies a wide range of high performance growing solutions worldwide securing good growing results for all types of plants in different growing conditions. The basis of Kekkilä Professional substrates is carefully selected, first-class Sphagnum peat harvested from our own peat bogs. Own peat raw material secures constant product quality throughout the season and from year to year.

TSM 2 W R6012 is a mix of raw materials from Sphagnum peat screened to Fine grade, limed and fertilised. High content of black peat secures a good water holding capacity under hot climates and therefore reduces the risk of wilting.

APPLICATION

Kekkilä TSM 2 W R6012 is a dark substrate with higher water holding capacity. Typically used for propagation of vegetable seedlings in plugs and trays up to 5 cm.

COMPOSITION

Peat raw material	Black peat 0.50 m ³ Sphagnum peat 0.50 m ³
Production screening	0–6 mm
Other constituents	

ADDITIVES

KS1 N-P₂O₅-K₂O 15-12-29 1.00 kg/m³
Limestone (Ca,Mg) 3.52 kg/m³
Wetting agent 0.11 l/m³

pH	pH (1+5 EN 13037)	5.9
	Press Water	5.5

CE	EC 1+5 EN 13038	32 mS/m
	Press Water	2.3 mS/cm